


SEPTIC TANKS IN POLYETHYLENE

A. Round

Type	Volume	Height	Diameter	Manhole	Height Inlet	Ø in/out	Height Outlet	Kg
SP1000	1.000 L	1.260	1.015	500	1.085	100	1.065	36
SP1500	1.500 L	1.570	1.260	500	1.305	100	1.265	50
SP2000	2.000 L	1.510	1.700	500	1.305	100	1.225	80
SP3000	3.000 L	1.940	1.700	500	1.745	100	1.645	130
SP5000	5.000 L	1.970	2.100	500	1.562	125	1.522	200



A

A. Round ECO (green)

Type	Volume	Height	Diameter	Manhole	Height Inlet	Ø in/out	Height Outlet	Kg
SP1000 ECO	1.000 L	1.260	1.015	500	1.085	100	1.065	36
SP1500 ECO	1.500 L	1.570	1.260	500	1.305	100	1.265	50
SP2000 ECO	2.000 L	1.510	1.700	500	1.305	100	1.225	80
SP3000 ECO	3.000 L	1.940	1.700	500	1.745	100	1.645	130
SP5000 ECO	5.000 L	1.970	2.100	500	1.562	125	1.522	200



B

B. Rectangular

Type	Volume	Height	Width	Length	Manhole	Height Inlet	Ø in/out	Height Outlet	Kg
SP1000RH	1.000 L	1.350	740	1.180	500	1.230	100	1.190	55
SP1500RH	1.500 L	1.350	740	1.810	500	1.230	100	1.190	100
SP2000RH	2.000 L	1.350	740	2.450	500	1.230	100	1.190	120



C

B. Rectangular ECO

Type	Volume	Height	Width	Length	Manhole	Height Inlet	Ø in/out	Height Outlet	Kg
SP1000RH ECO	1.000 L	1.250	720	1.235	500	1.150	110	1.110	56
SP1500RH ECO	1.500 L	1.480	720	1.880	500	1.320	110	1.280	75
SP2000RH ECO	2.000 L	1.650	880	2.020	500	1.500	110	1.450	90
SP3000RH ECO	3.000 L	1.700	880	2.630	500	1.500	110	1.450	120

C. Cylindrical, standing up)

Type	Volume	Height	Width	Manhole	Height	Ø in/out	Height	Kg	Height riser
SP1100	1.100 L	1.910	1.180	600	1.250	100	1.200	70	600
SP1600	1.600 L	2.250	1.290	600	1.500	100	1.450	80	600



D

D. Cylindrical, laying down)

Type	Volume	Height	Diameter	Length	Manhole	Height Inlet	Ø in/out	Height Inlet	Kg	Height Outlet
SP2400	2.400 L CE	1.950	1.350	2.350	600	1.220	125	1.180	120	600
SP3300	3.300 L CE	2.210	1.610	2.390	600	1.450	125	1.400	190	600
SP6000	6.000 L CE	2.470	2.070	2.400	600	1.850	125	1.800	290	600

E, F, G. Riser

Type	Foto	Height	Diameter	Weight (kg)
VHSP600/420	E	420	570	8
VHSP 500/600	F	600	500	5
VHRB 600/120-480	G	500	600	5.5



E



F



H



G

H. Boralit plastic pedestrian cover (Class A15)

Warranty: 10 years*

* Under conditions and strictly follow the installation procedures.

The dimensions are in mm and informatory. Subject to alterations.

Riser and PE-cover standard included for C and D.

Boralit NV

Nijverheidslaan 12 B-9880 Aalter - Belgium—2018

Tel.: + 32 (0)9 375 11 11 Fax: +32 (0)9 375 22 22

E-mail: sales@boralit.com

www.boralit.com

BORALIT

plastic tank solutions