



Boralit NV/SA  
Nijverheidslaan 12  
B-9880 AALTER  
Belgium

17

EN 12050-2

Wastewater lifting plant for faecal-free wastewater. Drainage of locations below flood level in buildings and sites to prevent any backflow of faecal-free wastewater into the building.

Product reference:		PP850/1/TOP 2 PP850/2/TOP 2 PP850/1/TOP 5 PP850/2/TOP 5 PP850/1/RXm 2/20 PP850/2/RXm 2/20 PP850/1/RXm 5/40 PP850/2/RXm 5/40 PP850/1/MCm 10/45 PP850/2/MCm 10/45 PP850/1/MCm 15/45 PP850/2/MCm 15/45
Material:		PE
Reaction to fire:		F
Water tightness:		No leakage
Effectiveness:	Pumping of solids:	No accumulation of solids
	Pipe connections:	DN50
	Ventilation:	DN100
	Minimum flow velocity:	0,7 m/s at 40 kPa
	Minimum solids passage:	10 mm
	Minimum useful volume:	10 L
Mechanical resistance:	Load bearing of tank:	10 kN
	Structural stability of tank:	No deformation
Noise level:		> 70 dB(A)
Durability:	Of water tightness:	No leakage
	Of lifting effectiveness:	No accumulation of solids
	Of mechanical resistance:	35 °C
Dangerous substances:		NPD