

ABOVE GROUND STORAGE TANKS (SINGLE WALL)

Description	Volume	Height mm	Width mm	Length mm	Weight
OP 1100	1.100 L	1.400	720	1.400	55
OP 1500	1.500 L	1.625	720	1.540	80
OP 2000	2.000 L	1.690	720	2.070	110
OP 2500	2.500 L	1.650	995	1.870	115
OP 3000	3.000 L	1.650	995	2.230	165
OP 4000	4.000 L	1.950	995	2.430	235



Dimensions are in mm and informative. Subject to alterations

The storage tanks are all equipped with hot galvanized reinforcement, A hermetic screw lid and have 1 (1.100 and 1.500 litre) or 3 (2.000 tot 4.000 litre) 2" F connections on top of the tank. They can be provided with a 2" F flange in metal or PP, at the bottom of the tank.

They can be connected with a special system of tubes. For this there are a bow, a T and an extension available. A bow is for the first tank. For each extra tank you need a T and an extension for tanks from 3.000 litre. On the last T you can put a flange in metal or PP of 2" F.

STORAGE AND TRANSPORT

The tanks are just a few years, resistant to UV rays. That is why it is recommended for placement in open air to provide a canopy or blocking. Install the tank on a horizontal (max. 1% slope), paved surface (concrete, vowels,...). Make sure that the surface is at least 10 cm longer and wider than the tank.

Do not place the tank on sharp objects like peddles and not near a heat source. Provide at least 10 cm between the tank and a wall.

Treat the tank carefully (especially in case of frost). Avoid shocks or bumping.

WARRANTY

We offer a 1-year warranty on all products of the Dehoust brand as far as evident manufacturing faults are concerned and excluding UV damage to unprotected tanks

Boralit NV

Nijverheidslaan 12 B-9880 Aalter - Belgium—2017

Tel.: + 32 (0)9 375 11 11 Fax: +32 (0)9 375 22 22

E-mail: sales@boralit.com

www.boralit.com

BORALIT

plastic tank solutions